

Sewing Glossary: How To Sew a Button Loop Tutorial

Description



In this easy tutorial we are going to show you how to sew a back slit and add a fabric button loop for closure. It is a really simple way to add a little interest to a closed up back of a top or a dress.


Materials



Fabric of your choice (we are using our beautiful IL042 903 FS Premier Finish 100% linen)

Matching sewing thread, one button, fusible interfacing

Tools



Pattern paper, ruler, pen, scissors, pins, fabric marker, needle, chalk, sewing machine

Time

1 hour


Difficulty

Beginner


Pattern

Draw your own pattern for the back slit facing in a few easy steps:


1. First, you need to decide how long you want your back opening to be. Letâ??s say we go for 5 inches. Draw a straight 5â?• line.



2. Add 3/8â?• on each side for the seam allowance and then another 3/4â?•.



3. Create a rounded shape respecting your measurements.




4. Using this pattern, cut one piece in fabric and one in fusible interfacing adding 3/8â?• (1 cm) seam allowance to the upper edge (so the final length of the middle vertical line would be 5 3/8â?•. Fuse both pieces together with your iron.

Steps


Note: Prewash your fabric and tumble dry it until it is still slightly moist, dry in room temperature. Iron the fabric so it is easier to work with.

Letâ??s start by making the fabric loop.


1. Mark out a small rectangle (1â?• wide and 3â?• long (2.5 cm x 7.5 cm)) on the bias of your fabric, in other words, at a 45 degree angle to the grainline. Cut it out.




2. Fold your rectangle in half lengthwise (right side facing out) and press. Then fold the raw edges in towards the folded center line and give it another press.




3. Fold it again in half lengthwise enclosing the raw edges and stitch over as close to the edge as possible.





You button loop is now ready but before attaching it to the back of your garment, you need to assemble the facing.

4. Cut your facing pieces (one from fabric and one from interfacing) using the pattern youâ??ve drawn. Apply the fusible interfacing to the wrong side of the fabric. Serge or zigzag the outer edge to prevent it from fraying.




5. Fold your facing in half to mark the center. Do the same with the back panel of your garment and pin the two centers right sides together.





6. Slide the button loop folded in half (the seam line should be turned inwards) under the left side of your facing and pin. Itâ??s important that you place it 3/8â?³Â• (neckline seam allowance) from the neckline edge (otherwise your loop will be caught in the neckline binding).







Basically, the loop is sandwiched between your dress/top and the facing. Adjust the length of the loop (make sure your button fits through) and leave 3/8â?• (1 cm) tails for the seam allowance

7. Topstitch the facing following the curved shape of your pattern.





8. Make a cut in the middle and clip to (but not through) the stitched line.



9. Press the facing away from the garment to open the seam.



10. Turn the facing to the wrong side and press to create a flat fold. Pin in place.



11. Edgestitch 1/4â?³Â• from the fold and give your back slit a good press.



12. The last step is to attach the button and you are all done!

Now all that you need to do is to sew shoulder and side seams of your garment together and finish the neckline and the armholes. You can either follow your pattern instructions, use a bias tape or check our tutorials here and here about different binding techniques.



Have a browse through our selection of linen and see which of our fabrics inspire you to use your new skill!

CATEGORY

1. SEWING ESSENTIALS
2. TUTORIALS

Category

1. SEWING ESSENTIALS
2. TUTORIALS

Date Created
September 16, 2016
Author
rima-khusainova