



Sewing Glossary: How To Attach Bias Tape Tutorial

Description



In our previous tutorials we have shown you two ways to cut and make your own bias tape: [the traditional method](#) (ideal for making small amounts of bias tape) and [the continuous method](#) (perfect for large amounts of bias tape). So now is the time to talk about two different ways to attach your bias tape to your garments.

You can add bias tape to anything you like: necklines, armholes, front openings, back openings, hems, etc. You can use it for quilt or blanket bindings, as a facing or even to finish your seams. It is also a great decorative detail that will bring a personal touch to any garment. Bias tape is

easy to attach if you know how. There are two methods to sew bias tape to a raw edge: the single-fold method and the double-fold method. In this tutorial we are going to show you how to sew the bias tape on and finish the ends both ways.

Both methods are great and it is hard to tell which one is best. We'll walk you through the steps, that way you'll know how to do both methods and can choose the way you prefer.

Materials & Tools



For the purpose of this tutorial, we are using two contrasting fabrics. [IL042 894 Premier Finish](#) for the bias tape and [IL019 ANTIQUE WHITE Softened](#) for the bodice.

Matching sewing thread (for the purpose of this tutorial we are using a contrasting white color thread), ruler, bias tape maker, fabric pen or chalk, scissors, sewing machine, iron

Difficulty

Beginner

Steps

Note: Prewash your fabric and tumble dry it until it is still slightly moist, let this dry in room temperature. Iron the fabric so it is easier to work with.

Make your bias tape using [the traditional method](#) or [the continuous method](#).

The Single-Fold Method

Single-fold bias tape is bias tape with each raw edge folded in toward the center, wrong sides together, and pressed.

1. Unfold your bias tape and pin the right side of one of its raw edges to the right side edge of your project aligning the two. Use as many pins as you need to make sure your curve is nice and smooth.



2. Stitch your bias tape to the fabric in the upper crease.



3. We recommend to trim the seam allowance to 1/4 but this step is optional.



4. Lightly press the seam toward the tape.



5. Carefully fold the tape over the stitching (to the wrong side of your fabric) taking care to cover the stitching as you fold. Press and pin.



6. Now back to the machine to topstitch the tape in place (from the right side) in the crease or as close to the bottom edge as you feel comfortable.



Joining The Ends

When you need to join two ends of a continuous bias strip, there are two

ways to do so that work great with both methods.

The first technique consists in unfolding your bias tape and stitching both ends right sides together. You'd want to pin the tape in place first but leave the tails unpinned. And then stitch them together where they meet.





Trim the ends and finger press the fold.





Then you refold the bias tape and continue stitching over the bottom edge to attach it to your project.

This technique is our preferred method since it'll give you the cleanest finish and best results.

However, there's another technique which is much easier and faster. The only disadvantage is that it makes a small lump that might get caught and torn open unless it is sewn shut.

With this second technique, you simply fold over a small seam allowance on one end and then slip the other raw end inside, overlapping the two.



Then you refold your bias tape and continue stitching over the bottom edge to attach it to your project.

Note: It's recommended to join the ends in an inconspicuous place: center back

for the neckline, underarm for the armholes, the back of your project where it's less visible or by matching the join to an already existing seam.

If you are applying bias tape to an edge that is not joined to anything, you simply extend the end of bias strip 1/4" beyond the edge to which it is being applied, trim the corners to reduce the bulk, fold the trimmed end over to the right side, re-fold the long edge and stitch over. Remember to backstitch to secure the end.





Bias Tape Facing Method

Did you know that you can use bias band to finish the edges in place of

facings? It is an excellent binding technique often used for necklines and armholes, that will give you a nice and clean finish and will keep any curves from standing away from your body. You can use whatever color fabric you like since it will not be visible on the outside of your garment.

The steps are the same as in the single fold method; the only difference is that instead of folding your second raw edge of the tape over to the right side to meet the seam line (basically, folding the middle section in two), you fold it all the way towards the wrong side and stitch in place.

You can check our binding tutorial [HERE](#) which will guide you through the process. Even though in the tutorial we are using just a simple bias strip, the steps are all the same.

The Double Fold Method

What is double fold bias tape you might ask? Well, it's very simple: a double fold bias tape is basically a single fold bias tape which has been folded in half lengthwise and pressed, with the single folds to the inside.



However, if you look closely at the store-bought double fold bias tape, you'll notice that one side is slightly wider than the other. This is done on purpose so that when you pin the wider edge to the wrong side of your project and then topstitch both layers at one from the right side, you'll be sure that the back section is caught in the seam.



Which is why it is very important when using your own custom-made bias tape, you press the tape in half lengthwise having one folded edge extending 1mm beyond the other.

1. So, with the double fold method, you simply slip the edge of the fabric between the folds of a bias tape, placing the raw edge against the center crease and the wider folded edge of the tape on the inside of your garment



Use pins to help hold the fabric and the bias tape together. This way, when you start sewing on the machine, nothing will slip out of place.

2. Follow the edge of the bias tape as you stitch it in place.



Give it a good press and admire your nice and clean finished edge!

Here's an extra little tip: bias tape is stretchy if you have to go around a curve, use your iron to press the curve in place before you get to the machine. It will give you a nice edge both on the front and the back as you go around those curves.

We hope that these tips on attaching bias tape will help you with your future projects! Next week we are going to show you how to bind mitered and inverted corners with your bias tape.

With all the possibilities of fabric and color choices, you can really add that extra personal touch to all your projects.

[Check out our whole selection here!](#)

CATEGORY

1. SEWING GLOSSARY
2. TUTORIALS

Category

1. SEWING GLOSSARY
2. TUTORIALS

Date Created

November 11, 2016

Author

rima-khusainova