
$\mathbf{F}|\mathbf{S}$  FABRICS-STORE.COM




Fred Knotted Crop Top Tutorial and Free Pattern

# Description











Is it just us, or has the tie-back crop top been all over Instagram this summer? To embrace the trend, we are offering you this new sewing pattern that is really easy to make and would make a lovely addition to your wardrobe. Use the adjustable ties to create a flirty bow in the back. The cut is just plunge-y enough to feel sexy without feeling too exposed. And the best part is that it is fully lined, with no apparent seams. Pair it with high-waisted jeans or skirts.


#### Materials



2 yards of IL020 Bleached Softened Lightweight Linen

Matching sewing thread

### **Tools**



Scissors, pins, ruler, chalk, measuring tape, fabric marker, sewing machine

# **Difficulty**

Beginner

### **Time**

3-4 hours

### Pattern

You can access the multi-sized printable PDF pattern by following this link HERE. All seam allowances are included. The model is wearing US size 6.

If you need help adjusting the pattern for a fuller bust, we have a great Full Bust Adjustment tutorial <u>HERE</u>.

## Steps

Note: Prewash your fabric and tumble dry it until it is still slightly moist, dry in room temperature. Iron the fabric so it is easier to work with.

Since the top is completely lined, you'll need to sew two identical bodices: one in lining and one in main fabric.

Let's start with the main fabric.

1. First, sew the darts. Carefully fold the darts with right sides together, pin and stitch in place. Leave long tails at the apex of your dart and tie little knots to secure. Press the darts downward.





2. With right sides together, pin the front and the back of your top at the shoulder seams.



3. Sew at a 3/8" seam allowance and press the seams open. Remember to

backstitch at the start and finish of the seams. No need to serge/zigzag raw edges since all the seam allowances will be enclosed between the layers.



4. Pin and sew the side seams right sides together at the usual 3/8" (1 cm) seam allowance and press the seams open.







5. Repeat steps 1-4 with the lining pieces.

6. Pin the main fabric and the lining right sides together matching the raw edges and the seams.



7. Stitch around all edges except the armholes at a 3/8" (1 cm) seam allowances and leave a small 2" opening at the hem.

 $\mathbf{F}|\mathbf{S}$  FABRICS-STORE.COM





When you come to the V, pivot your need and run one small horizontal stitch right at the bottom of the V. This will help achieve a smoother point when you turn the fabric right side out.

 $\mathbf{F}|\mathbf{S}$ 

8. Trim the stitched seam allowances down to 1/4 and clip the V to release the tension.



- 9. Finger press the seams open and turn the fabric right side out through the opening at the hem.
- 10. Use a lot of steam and press the edges flat rolling the seam slightly to the inside.

FABRICS-STORE.COM







11. Tuck in and press the armholes seam allowance and the hem at the opening. Pin.

 $\mathbf{F}|\mathbf{S}$  FABRICS-STORE.COM





12. The last step is to topstitch around all edges (neckline, armholes, ties and bottom hem) 1/8" from the seams to close the openings, stabilize the edges and keep them in place.



Give your finished top one last press and you are all done!

We love seeing what you make! Don't forget to share your pictures and tag your creations with #FabricsStoreFredPattern hashtag.

Check out <u>our selection</u> of linen and see which of our fabrics inspire you for this project. This little top will look great in any color, pattern or weight!

#### **CATEGORY**

- 1. FREE PATTERNS
- 2. TUTORIALS

## Category

- 1. FREE PATTERNS
- 2. TUTORIALS

# Date Created

September 20, 2018

#### **Author**



## rima-khusainova